

We MERSEN USA EP Corp.
374 Merrimac Street Newburyport, MA 01950 USA

Certify that products with the registered trade mark Mersen Ferraz Shawmut

Product type Medium Voltage IEEE Fuses
General Purpose Clip-Lock Fuses for Transformer Protection

Model Series Line 5.5kV Clip-Lock Mount Transformer Fuses

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided below is based on data obtained through ongoing due diligence with our suppliers. In some cases, the information may not yet represent full coverage of our supply chain. Mersen reserves the right to update or amend this declaration as additional data becomes available, or verification processes are completed.

This declaration is not an EU or UKCA declaration of conformity, Mersen USA EP Corp. is providing RoHS conformity to all product ranges even if they are out of the scope of the directive with the same level of compliance on substances restrictions and corresponding exemptions.

Date / Location : 18.02.2026 / Newburyport

Name : Tim KAPPEN

Position / Signature :

Sr. Manager Quality
For the president and by delegation

COMP-015276

Catalog number list

Item number	ROHS exemption
A055C1D0R0-10E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-15E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-20E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-25E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-30E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-40E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-50E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-65E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-80E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-100E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-125E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-150E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-200E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-250E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-300E	6(c) - Copper alloy containing up to 4% lead by weight
A055C1D0R0-400E	6(c) - Copper alloy containing up to 4% lead by weight
A055C2D0R0-450E	6(c) - Copper alloy containing up to 4% lead by weight
A055C2D0R0-500E	6(c) - Copper alloy containing up to 4% lead by weight
A055C2D0R0-600E	6(c) - Copper alloy containing up to 4% lead by weight