RoHS COMPLIANCE STATEMENT

We MERSEN FRANCE SB
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

Certify that products with the registered trade mark Mersen

Product type High-Speed and Semiconductor protection fuses
Square Body High-Speed Fuse-Links DC Protection

Model Series Line Protistor® size 120 gR , 750VDC (IEC)

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:
RoHS directive N° 2011/65/UE
RoHS directive N° 2015/863
https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

Date / Location : 17.04.2026 / Saint Bonnet de Mure

Name : Pierre LAVAUD

Position / Signature : Head of R&D department
For the president and by delegation
Pierre Lavaud

COMP-016109

Catalog number list

Catalog number	Item number	ROHS exemption
D120GC75V100EF	P085205	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V125EF	R086242	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V160EF	N085204	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V50EF	Y084776	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V63EF	R085207	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V80EF	Q085206	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V100TF	R082401	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V125TF	P085251	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V160TF	R085253	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V50TF	B220824	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V63TF	Q082400	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
D120GC75V80TF	Z090435	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)