

We MERSEN FRANCE SB
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

Certify that products with the registered trade mark Mersen

Product type High-Speed and Semiconductor protection fuses
Square Body High-Speed Fuse-Links AC Protection

Model Series Line Protistor® size 73 gR, 690VAC (IEC)

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

Date / Location : 16.04.2026 / Saint Bonnet de Mure

Name : Pierre LAVAUD

Position / Signature :

Head of R&D department
For the president and by delegation



Catalog number list

Catalog number	Item number	ROHS exemption
PC73GB69V450D1A	W236298	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V500D1A	W302216	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V550D1A	R302672	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V630D1A	X236299	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V700D1A	F301765	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V800D1A	B236073	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V10CD1A	S302673	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V315EF	C301348	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V400EF	D301349	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V450EF	E301350	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V550EF	F301351	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V630EF	G301352	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V700EF	H301353	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact

		fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V10CTF	F301719	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V315TF	W301342	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V350TF	B301715	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V400TF	X301343	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V450TF	Y301344	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V500TF	C301716	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V550TF	Z301345	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V630TF	A301346	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V700TF	B301347	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V800TF	D301717	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)
PC73GB69V900TF	S301638	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for Flush end contact fuse only) 7(a) - for lead alloys (High temperature solder)