

**We** MERSEN FRANCE SB  
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

**Certify that products with the registered trade mark Mersen**

**Product type** High-Speed and Semiconductor protection fuses  
High performance square body fuse-links AC protection

**Model Series Line** Protistor® size 91 aR , 1500VAC

**References** please refer to page 2 for catalog number

**comply with the EU RoHS (Restriction of Hazardous Substances) Directives:**

**RoHS directive N° 2011/65/UE**

**RoHS directive N° 2015/863**

[https://ec.europa.eu/environment/waste/rohs\\_eee/index\\_en.htm](https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm)

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

**Any exemptions are listed below and exemption validity dates are monitored by Mersen.**

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

**Date / Location :** 16.04.2026 / Saint Bonnet de Mure

**Name :** Pierre LAVAUD

**Position / Signature :**

Head of R&D department  
For the president and by delegation



## Catalog number list

Catalog number	Item number	ROHS exemption
PC91UF15C100TF	W076149	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C125TF	X076150	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C160TF	Y076151	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UG15C200TF	A076153	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C250TF	C076155	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C315TF	D076156	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C350TF	E076157	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UK15C225TF	B076154	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C100D4A	V221232	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C125D4A	M210737	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C125D4F	A076061	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C160D4A	L077037	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UF15C160D4F	B076062	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse

		only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UG15C200D4A	A221214	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UG15C200D4F	D076064	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C250D4A	D221309	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C250D4F	T076101	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC91UH15C315D4F	V076102	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)