

We MERSEN FRANCE SB
15, Rue Jacques de Vaucanson 69720 SAINT BONNET DE MURE FRANCE

Certify that products with the registered trade mark Mersen

Product type High-Speed and Semiconductor protection fuses
High performance square body fuse-links AC protection

Model Series Line Protistor® size 93 aR , 1500VAC

References please refer to page 2 for catalog number

comply with the EU RoHS (Restriction of Hazardous Substances) Directives:

RoHS directive N° 2011/65/UE

RoHS directive N° 2015/863

https://ec.europa.eu/environment/waste/rohs_eee/index_en.htm

and declare that the materials and the processes used to manufacture the above-mentioned parts do not contain any of the restricted substances beyond their specified limit at homogeneous material level as mentioned in the table:

Sl. No.	RoHS Restricted Substances	Max. Concentration
1.	Cadmium	0.01%
2.	Mercury	0.1%
3.	Lead	0.1%
4.	Chromium VI	0.1%
5.	Polybrominated biphenyls (PBB)	0.1%
6.	Polybrominated diphenyl ethers (PBDE)	0.1%
7.	Bis(2-ethylhexyl) phthalate (DEHP)	0.1%
8.	Butyl benzyl phthalate (BBP)	0.1%
9.	Dibutyl phthalate (DBP)	0.1%
10.	Di-isobutyl phthalate (DIBP)	0.1%

Any exemptions are listed below and exemption validity dates are monitored by Mersen.

The information provided is based upon data obtained from ongoing due diligence concerning goods and materials provided by our suppliers. Mersen reserves the right to update and modify this communication, as it believes necessary or appropriate.

Date / Location : 16.04.2026 / Saint Bonnet de Mure

Name : Pierre LAVAUD

Position / Signature :

Head of R&D department
For the president and by delegation



Catalog number list

Catalog number	Item number	ROHS exemption
PC93UB15C750TF	X076173	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C230TF	L097829	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C250TF	M076164	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C315TF	N076165	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C350TF	P076166	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UG15C375TF	Q076167	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UH15C630TF	V076171	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UJ15C700TF	W076172	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C400TF	R076168	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C500TF	T076170	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UB15C750D4F	S076123	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C315D4F	L076071	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UF15C350D4F	M076072	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse

		only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UG15C375D4F	N076073	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UH15C630D4F	A076107	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C400D4F	P076074	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C450D4A	J078277	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C450D4F	Q076075	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)
PC93UK15C500D4F	R076076	6(b) - for aluminum alloys (signalization pin) 6(c) - for copper alloys (Brass for flush end contact fuse only and silicate plug) 7(a) - for lead alloys (High temperature solder)